


# CABLE MARKERS

1



## Z-TYPE® MARKERS

- Expanding gusset
- Wide size range
- Various pack styles to suit your production requirements
- Straight or chevron cut
- Colour coding option enables identification when mark is obscured
- Pre-print service also available, contact Tyco Electronics

The Z-Type® marker has an expanding gusset which enables each size of marker to accommodate a wide range of cable sizes. The size range allows marking of cables from less than 0.5mm<sup>2</sup> to 35mm<sup>2</sup>. As well as straight cut, chevron cut markers are available for interlocking and alignment of mark. Z-Type® markers are also available colour coded to BS6746C:1993.

A customised service for Z-Type® and K-Type® (see overleaf) markers is also available. Customised markers

may be printed sequentially, numerically or alphabetically, and include any combination of characters and character height. Special symbols may also be produced. All marks can be packed in the order of use. For more information telephone +44 (0) 1527 540 400.


### SERVICE TEMPERATURE RANGE:

–45°C to +70°C.

**MATERIAL:** Plasticised PVC.

**MARKS AVAILABLE:** A-Z, 0-9, +, -, /, phase, earth, blank and full stop.

# CABLE MARKERS



## Z-TYPE® MARKERS – STRAIGHT CUT AND CHEVRON CUT

For Cable dia mm	For Cable size* mm <sup>2</sup> (BS6004) (BS6231)	Marker size	Marker length mm	Packed		Order code (Straight cut)	Order code (Chevron cut)
				Reel (R) Box (A)	Pancake Reel (PR)		
1.5 – 2.0	–	5	4.5	1000	–	0580	<b>1151</b>
2.0 – 3.2	1.0	7	4.5	1000	–	0581	<b>1152</b>
2.5 – 4.0	1.5	9	4.5	1000	250	0615	<b>1153</b>
2.9 – 4.7	2.5	11	4.5	1000	250	0616	<b>1154</b>
3.4 – 5.7	4.0	13	4.5	1000	200	0617	<b>1155</b>
3.8 – 6.3	6.0	15	4.5	1000	150	0618	<b>1156</b>
4.3 – 6.9	10.0	18	4.5	500	150	0620	<b>1157</b>
5.5 – 8.9	16.0	23	6.0	500	75	0622	<b>1158</b>
7.9 – 12.7	25.0	35	6.0	250	50	0624	<b>1159</b>

\*Application to cables BICC Ref. No. 6491X

### COLOUR OPTIONS (STRAIGHT CUT)

**White body marked black:** A-Z, 0-9 and symbols, available on reels (R) in boxes (A) and on pancake reels (PR).

**Yellow body marked black:** A-Z, 0-9 and symbols, available on reels (R) only.

**Colour coded:** 0-9 all sizes, available in boxes (A). 0-9 box pack (100 off each number) also available.

### COLOUR OPTIONS (CHEVRON CUT)

**White body marked black:** A-Z, 0-9 and symbols, available in boxes (A) only.

**Yellow body marked black:** A-Z, 0-9 and symbols, available on reels (R) only.

**Colour coded:** 0-9, size 11 only, available in boxes (A) or on reels (R).

### MATERIAL PPVC.

**SERVICE TEMPERATURE RANGE**  
–45°C to +70°C.

### CHEMICAL RESISTANCE

**Excellent:** Aircraft Fuel, Propan-2-ol, 1,1,1 Trichloroethane, Kilfrost Silicone Hydraulic Fluid **Poor:** Aeroshell (4), Sullage Fluid, Gas Turbine Oil 98. **Poor:** Skydrol 500 B4



## K-TYPE® MARKERS

For Cable dia mm	For Cable size* mm <sup>2</sup> (BS6004) (BS6231)	Marker size	Marker length mm	Packed (R) Reel	Order code
4.2 – 7.0	4.0 – 10.0	65†	6.0	500	<b>1361</b>

\*Application to cables BICC Ref. No. 6491X

†Other sizes available on request.

### COLOUR OPTIONS

**Yellow body or white body marked black:** A-Z, 0-9 and symbols, available on reels (R) only.

**Colour coded:** 0-9 available on reels (R) only.

**MATERIAL**  
PPVC.

**SERVICE TEMPERATURE RANGE**  
–45°C to +70°C.


### CHEMICAL RESISTANCE

**Excellent:** Aircraft Fuel, Silicone Hydraulic Fluid, Propan-2-ol, Kilfrost Fluid 1,1,1, Trichloroethane, Petrol, 50% Sodium Chloride, White Spirit, Tap Water, Sea Water, 10%

Detergent Solution, Diesel Fuel, Diala Oil B, Diethyl Ether, Ammonium Hydroxide. **Good:** Aeroshell (4), Sullage Fluid, Gas Turbine Oil 98, Methanol, 20% Sodium Hydroxide. **Poor:** Skydrol 500 B4, Hydrochloric Acid, Acetone.

# CABLE MARKERS

1



## Z-TYPE® MARKERS Straight and Chevron Cut

Cable diameter																				
mm	0.5	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0				
Cable size* mm²				1.0	1.5	2.5	4.0	6.0		10.0	16.0		25		35		50		70	
5			■																	
7				■	■															
9					■	■	■													
11						■	■	■												
13							■	■	■	■										
15								■	■	■	■									
18									■	■	■	■								
23										■	■	■	■	■						
35											■	■	■	■	■	■	■	■	■	■


\*Application to cables BICC Ref. No. 6491X



## K-TYPE® MARKERS

Cable diameter																				
mm	0.5	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0				
Cable size* mm²				1.0	1.5	2.5	4.0	6.0		10.0	16.0		25		35		50		70	
65										■	■	■	■	■	■	■	■	■	■	■

\*Application to cables BICC Ref. No. 6491X



## O-TYPE™ MARKERS BS3858: 1992 TYPE3

Cable diameter																				
mm	0.5	1.0	2.0	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0	14.0	15.0				
Cable size* mm²				1.0	1.5	2.5	4.0	6.0		10.0	16.0		25		35		50		70	
0.75		■																		
10			■																	
12				■																
15					■															
20						■														
25							■													
30								■	■											
40									■	■	■									
55										■	■	■	■	■	■	■	■	■	■	■

\*Application to cables BICC Ref. No. 6491X