

## RAYCHEM HEATSHRINK

# Raychem



MWTM, a heat-shrinkable medium-wall tubing now in widespread use in terminations, joints and cable repairs throughout the world. Heating with a commonly available gas torch activates the tubing's "elastic memory"

Part No	Length	Cable Range	Expand Dia	Recovered Dia
MWTM 10/3	1.2M	3.5 to 9	10mm	3mm
MWTM 16/5	1.2M	5.5 to 14.5	16mm	5mm
MWTM 25/8	1.2M	9 to 22.5	25mm	8mm
MWTM 35/12	1.2M	13 to 31.5	35mm	12mm
MWTM 50/16	1.2M	17.5 to 45	50mm	16mm
MWTM 63/19	1.2M	21 to 57	63mm	19mm
MWTM 75/22	1.2M	24 to 68	75mm	22mm
MWTM 85/25	1.2M	27.5 to 77	85mm	25mm



WCSM is a heat-shrinkable heavy-wall tubing for insulating and sealing power cables and accessories. In WCSM tubing, the electrical and physical properties of a cable oversheath material are combined with ruggedness and easy installation.

Part No	Length	Cable Range	Expand Dia	Recovered Dia
WCSM 13/4	1.2M	4.5 to 11	13mm	4mm
WCSM 20/6	1.2M	6.8 to 17.5	20mm	6mm
WCSM 33/8	1.2M	9 to 30	33mm	8mm
WCSM 43/12	1.2M	13 to 39	43mm	12mm
WCSM 51/16	1.2M	17.5 to 44	51mm	16mm
WCSM 70/21	1.2M	23 to 62	70mm	21mm
WCSM 85/25	1.2M	27 to 76.5	85mm	25mm

# RAYCHEM HEATSHRINK

## Raychem



### DWP-125

#### **Flexible, high-shrink-ratio, adhesive-lined, polyolefin tubing**

\*3:1 shrink ratio allows insulation and sealing of irregular shapes.

\*Medium wall provides increased mechanical protection while maintaining flexibility when installed.

\*Adhesive bonds to a wide variety of plastics, rubber and metals (including polyethylene, neoprene & steel).

\*Operation temperature range -40 c to 110 c.

Part No	Length	Colour	Expand Dia	Recovered Dia
DWP125-3.2-0	1.2M	Black	3.2mm	1mm
DWP125-4.8-0	1.2M	Black	4.8mm	1.5mm
DWP125-6.4-0	1.2M	Black	6.4mm	2mm
DWP125-9.5-0	1.2M	Black	9.5mm	3mm
DWP125-12.7-0	1.2M	Black	12.7mm	4mm
DWP125-12.7-2	1.2M	Red	12.7mm	4mm
DWP125-19.1-0	1.2M	Black	19.1mm	8mm
DWP125-19.1-2	1.2M	Red	19.1mm	8mm
DWP125-25.4-0	1.2M	Black	25.4mm	13mm
DWP125-25.4-2	1.2M	Red	25.4mm	13mm
DWP125-38.1-0	1.2M	Black	38.1mm	13mm
DWP125-50.8-0	1.2M	Black	50.8mm	20mm



# Raychem

## HEATSHRINK ON A REEL 2:1 RATIO


Supplied in a carton dispenser providing easy storage & handling facilities.

Colours - Black, Blue, Red, White, Clear. (Green/Yellow Available)

<b>PART No.</b>	<b>EXPANDED DIA</b>	<b>RECOVERED DIA</b>	<b>QTY MTS</b>
HSB 3	3.2mm	1.6mm	20
HSB 4	4.8mm	2.4mm	10
HSB 6	6.4mm	3.2mm	10
HSB 9	9.5mm	4.8mm	8
HSB 12	12.7mm	6.4mm	8
HSB 19	19.1mm	9.5mm	5
HSB 25	25.4mm	12.7mm	5



## HEATSHRINK KIT



Colours: black, red, blue, white, clear & green/yellow.

<b>PART No.</b>	<b>LENGTH</b>	<b>DESCRIPTION</b>
REMKIT1	100mm	This kit contains assorted colours of GPT: 2.4, 3.2, 4.8, 6.4, 9.5, 12.7 & 19.1

## VERSAFIT-3X SPOOLS 3:1 SHRINK RATIO

Raychem's Versafit - 3x heat-shrinkable tubing has a 3:1 shrink ratio for use where a large expansion is required to accommodate dimensional differences.

Versafit - 3x tubing is a specially formulated, cross-linked polyolefin with a low recovery temperature, excellent flexibility & high flame-retardant.

Colour - Black



<b>PART No.</b>	<b>IMPERIAL DIA Inches</b>	<b>EXPANDED "D" DIA mm</b>	<b>RECOVERED "d" DIA mm</b>	<b>STD SPOOL LENGTH</b>
VERSA-2.4-0	3/32	2.4	0.8	152m
VERSA-3.2-0	1/8	3.2	1.1	152m
VERSA-6.4-0	1/4	6.4	2.2	76m
VERSA-9.5-0	3/8	9.5	3.2	61m
VERSA-12.7-0	1/2	12.7	4.3	45m
VERSA-19.1-0	3/4	19.1	6.4	76m
VERSA-25.4-0	1	25.4	8.5	76m

**(Also available on smaller spools)**