

Web www.gvk.com.au Email sales@gvk.com.au Phone

BI-METAL SECTOR LINKS BKS

- 1. Tick a box to identify the standard blank which is closest to your required design.
- 2. Complete the Conductor Details section inserting your requirements. Please note all details are mandatory.
- 3. Enter your required dimensions staying within the guidelines in the standards table.
- 4. Complete customer contact and authorisation details. Please note all details are mandatory.
- 5. Fax to Utilux Custom Connectors.

E:

Comments:



1. STANDARDS & GUIDELINES All dimensions in mm Catalogue No. Conductor **Conductor Range** Copper - F L **Length Max** Sector mm² Copper - mm² Max □ BKSX 35-240 16-300 160 65

2.

2. CONDUCTOR DETAILS									
	SECTOR END: MATERIAL - AI				SMALL END: MATERIAL - Cu				
	3 Core	☐ 35mm²	50mm²	70mm²		Metric	Imperial	Area:	mm²/in²
	4 Core	☐ 95mm²	120mm²	☐ 150mm²		Flexible		Stranding:	
		☐ 185mm²	☐ 240mm² ☐ Compacted		ted				
						Other			
3. REQUIRED SPECIFICATIONS									
Dimensions: (IF NON-STANDARD)									

Qty:

INTERNAL SALES USE ONLY 4. CUSTOMER DETAILS Part No: BKS Company: Requested by: **Sales Order No:** Tel: **Drawing No: Purchase Order No: Entered by:**

5. FAX THIS FORM TO UTILUX CUSTOM CONNECTORS - (03) 9312 6433