

# Wiha Torque VDE Screwdrivers.

Precise and High Repeat Accuracy.



All drivers individually tested protective insulation  
1,000 V AC, VDE and GS tested

PROUDLY DISTRIBUTED BY



Web: www.gvk.com.au  
Email: sales@gvk.com.au  
Phone: 03 9312 6633  
Fax: 03 9312 6433



## SlimBits.



### 2831-10 SoftFinish® electric slimBit, slotted.

Standards: Manufactured acc. to IEC 60900:2004.  
Material: High-quality chrome vanadium steel, through-hardened, bronzed. Protective insulation moulded directly onto the bit and completely integrated into the blade in the lower area from size 4.0.  
Application: For all work on or around electrical components up to 1000 V AC.  
Extra: The integrated protective insulation enables low-lying fastening and spring elements to be reached and manipulated. The slim form of the bit allows easy reaching of the screws below the finger and hand guards.  
Attention: 6 mm slimBits only to be used in the slimVario bit holder and slimTorque VDE bit holder (VDE torque system).

Order-No.	⌀	↔	⊕	⊙		▬
34578	2,5	75	0,4	6,0	no slim version	1
34579	3,0	75	0,5	6,0	no slim version	1
34580	4,0	75	0,8	6,0		1
34581	5,5	75	1,0	6,0		1
34582	6,5	75	1,2	6,0		1



### 2831-11 SoftFinish® electric slimBit, Phillips.

Order-No.	⊕	↔	⊙	▬
34583	PH1	75	6,0	1
34584	PH2	75	6,0	1



### 2831-12 SoftFinish® electric slimBit, Pozidriv.

Order-No.	⊕	↔	⊙	▬
34585	PZ1	75	6,0	1
34586	PZ2	75	6,0	1



### NEW 2831-17 SoftFinish® electric slimBit, square (Robertson).

Order-No.	⊙	⊕	↔	⊙	▬
35510	Robertson 1	2,3	75	6,0	1
35511	Robertson 2	2,8	75	6,0	1



### NEW 2831-13 SoftFinish® electric slimBit, Xeno, for terminal screws (slotted/ Phillips)

Order-No.	⊕	↔	⊙	▬
34587	SL/PH1	75	6,0	1
34588	SL/PH2	75	6,0	1



### 2831-14 SoftFinish® electric slimBit for terminal screws (slotted/Pozidriv).

Order-No.	⊕	↔	⊙	▬
34589	SL/PZ1	75	6,0	1
34590	SL/PZ2	75	6,0	1



### NEW 2831-15 SoftFinish® electric slimBit, TORX®

Order-No.	⊕	↔	⊙	▬
35506	T8	75	6,0	1
35507	T10	75	6,0	1
35508	T15	75	6,0	1
35509	T20	75	6,0	1
36071	T25	75	6,0	1

## Torque Set.



Order-No.	Series	▬
36078	2872 T10	1
	2872	TorqueVario®-S VDE torque screwdriver, Model 1.0 – 5.0 Nm
	2831-00	SoftFinish® electric slimVario bit holder with handle and ClicFix, 6.0 mm.
	2879	slimTorque VDE bit holder for 6 mm slimBits.
	285-900	Torque-Setter
⊕	2831-10	1x4,0 1x5,5
⊕	2831-11	1xPH1 1xPH2
⊕	2831-12	1xPZ1 1xPZ2

## TorqueVario®-S VDE. SlimTorque VDE bit holder.



2872 TorqueVario®-S VDE torque screwdriver. Insulation up to 1,000 V AC, GS-mark. Torque value can be set via window scale. Automatic release.

Order-No.	Nm	⚡%	⊕	↔	⊙	▬
26625	0.6-2.0	6%	3.8	131	30	1
26626	1.0-5.0	6%	3.8	138	36	1
26627	2.0-8.0	6%	3.8	142	41	1