

Web www.gvk.com.au Email sales@gvk.com.au Phone 03 9312 6633 Fax 03 9312 6433

BI-METAL STALK LUGS BS

- 1. Tick a box to identify the standard blank which is closest to your required design.
- 2. Complete the Conductor Details section inserting your requirements. Please note all details are mandatory.
- **3. Enter your required dimensions** staying within the guidelines in the standards table.
- 4. Complete customer contact and authorisation details. Please note all details are mandatory.
- 5. Fax to Utilux Custom Connectors.





1.	STANDARDS & GU	All dimensions in mm				
	Catalogue No.	Conductor Range mm ²	D Max	E - Cu Max	F - Al Max	L Max
	BSX10-35/1	10-35	12	30	32	70
	BSX50-70/1	50-70	16	30	32	70
	BSX95-120/1	95-120	22	50	60	120
	BSX150-185/1	150-185	26	50	60	120
	BSX240-300/1	240-300	33	50	60	120
	BSX400-630/1	400-500	45	70	70	160

■ Metric ■ Imperial ☐ Flexible Area: mm²/in² Compacted Stranding:

2. CONDUCTOR DETAILS

Comments:

■ Other

3. REQUIRED SPECIFICATIONS

Stalk Diameter (D):	mm
Dimensions: (IF NON-STANDARD)	
E:	mm
F:	mm
Qty:	
	mm

4. CUSTOMER DETAILS

Company: Requested by: Tel: **Purchase Order No:**

INTERNAL SALES USE ONLY

Part No: BS **Sales Order No: Drawing No: Entered by:**

5. FAX THIS FORM TO UTILUX CUSTOM CONNECTORS - (03) 9312 6433